

4.2mm(.165")Wire To Wire And Wire To Board Connector





SPECIFICATIONS:

- Current Rating:9AAC,DC
- Voltage Rating:600V AC,DC
- Operating Temperature:V2:-25°C~+85°C
V0:-40°C~+105°C
- Contact Resistance:10mΩ max.
- Insulation Resistance:1000MΩ Min.
- Withstanding Voltage:1500V AC/minute
- Material:Housing:Nylon66 UL94V-2/UL94V-0
Pin:Brass.Tin plated
- Pin In Housing Retention Force Requirement:3.5kg (Min.)

Shenzhen Hongru Connector Co., Ltd

Email:yukyli@hrb-connector.com
Tel: 86-0755 2709 6669
Fax: 86-0755 2709 2392
Skype: haiyuncheng-vivian
Mobile(whatsapp): 86-186 8112 3590
Website: <http://www.hrb-connector.com>



Ordering Information And Dimensions

Part NO.			Dimensions			Part NO.			Dimensions		
TYP UL94V-0	TYP UL94V-2	Circuits	Dim:A	Dim:B	Dim:C	TYP UL94V-0	TYP UL94V-2	Circuits	Dim:A	Dim:B	Dim:C
M4257R-2x1-A	M4257R-2x1-B	2	/	5.40	/	M4257R-2x7-A	M4257R-2x7-B	14	25.20	30.80	25.20
M4257R-2x2-A	M4257R-2x2-B	4	4.20	9.60	4.20	M4257R-2x8-A	M4257R-2x8-B	16	29.40	35.00	29.40
M4257R-2x3-A	M4257R-2x3-B	6	8.40	14.00	8.40	M4257R-2x9-A	M4257R-2x9-B	18	33.60	39.20	33.60
M4257R-2x4-A	M4257R-2x4-B	8	12.60	18.20	12.60	M4257R-2x10-A	M4257R-2x10-B	20	37.80	43.40	37.80
M4257R-2x5-A	M4257R-2x5-B	10	16.80	22.40	16.80	M4257R-2x11-A	M4257R-2x11-B	22	42.00	47.60	42.00
M4257R-2x6-A	M4257R-2x6-B	12	21.00	26.60	21.00	M4257R-2x12-A	M4257R-2x12-B	24	46.20	51.80	46.20